

suprema

BioEntry Plus

IP based Fingerprint Access Control



| BioEntry Plus | BioEntry Plus is an IP based fingerprint access control device featuring easy installation and user friendly operations. Integrated with both fingerprint and proximity card, BioEntry Plus covers a full range of access control applications from a simple standalone door control to complex networked access control systems



Suprema BioEntry Plus

IP based Fingerprint Access Control

Features

Fast and accurate fingerprint identification

- * Award winning fingerprint algorithm (No. 1 in FVC2004 & FVC2006)
- * 1:2000 fingerprint identification in 1 second

Easy installation and connectivity

- * Ethernet interface for TCP/IP communication
- * Wiegand output configurable up to 64 bits
- * Internal relay for direct lock interface

Easy operation and management

- * Built-in smartcard card reader for different user authentication modes (fingerprint and/or card)
- * Easy-to-use Windows Based Software (BioStar) access control and time attendance
- * Optional standalone user management using administrative cards
- * Template on card to store fingerprint data on a smart card

Slim and elegant design

- * Slim design for installation on a door frame
- * Multi color LED and multi-tone audible alerts for intuitive user interface

Full access control features

- * 128 access groups and 128 time schedules
- * Anti-passback door zones supporting 32 readers
- * Tamper switch and duress finger option

External relay unit

- * Secure door control and I/O expansion

Specifications

CPU	400MHz DSP	400MHz DSP
Memory		4MB flash + 8MB RAM
Fingerprint sensor		500 dpi optical sensor
Identification speed		2,000 match in 1 second
Fingerprint capacity		10,000 templates (5,000 users)
Log capacity		50,000 events
RF card		Proximity (125kHz EM), Mifare (13.56MHz)
Operation modes		Fingerprint, RF card, RF card + fingerprint
Network interface		TCP/IP, RS485
Wiegand output		Configurable up to 64 bits
TTL I/O		2 inputs for exit switch and door sensor
Internal relay		Deadbolt, EM lock, door strike, automatic door
Sound and interface		Multi-color LED and multi-tone buzzer
Operating voltage		12VDC
Size		50 x 160 x 37mm (W x H x D)

Model Information

Model	Fingerprint Sensor	
	OC (Optical Sensor)	TC (Capacitive)
BioEntry Plus	BEPL-OC	NA
BioEntry Plus Mifare	BEPM-OC	BEPM-TC


Secure I/O

- Accessory unit for secure door control and I/O expansion
- Encrypted communication with BioEntry Plus for enhanced security

- * 16MHz 8bit microprocessor
- * 4 digital inputs and 2 relay outputs
- * Size : 143 x 82 x 35 mm (W x H x D)



System Configuration



Intelligent Biometric Controls, Inc.

601A Brooklyn Dr Milford, OH 45150

Tel : 866-400-9292 Fax : 513-239-3628

E-mail : sales@fingerprintdoorlocks.com Homepage : www.FingerprintDoorLocks.com

