

9500

Series

The completely surface
mounted, fire-rated solution

hes
ASSA ABLOY

Specifications

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- WHI fire door listed
- UL 1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1 (#E09371, #E09372, #E09373)
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- UBC-7-2-94, Uniform Building Code
- Patent #6,390,520

Standard Features

- Completely surface mounted
- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail safe/fail secure
- Dual voltage 12 or 24 VDC
- Horizontal adjustment
- Non-handed
- Internally mounted solenoid
- Accommodates up to 3/4" pullman latch
- Five year limited warranty

Optional Features

- LBM - Latchbolt monitor
- LBSM - Latchbolt strike monitor

Electrical

- .45 Amps @ 12VDC continuous duty
- .25 Amps @ 24VDC continuous duty

Finishes

- 630 - Satin stainless steel
- 605 - Bright brass
- 606 - Satin brass
- 612 - Satin bronze
- 613 - Bronze toned
- 629 - Bright stainless steel

Frame Application

- Metal
- Wood

