

# 9600

## Series

Sets the standard for strong, reliable  
surface mount electric strikes



## Specifications

- UL listed to ANSI 250.13 Severe Windstorm •
- UL1034 burglary-resistant listed •
- ANSI/BHMA, A156.31 Grade 1 (#E09731, #E09732) •
- Patent #6,390,520 •

## Standard Features

- Completely surface mounted •
- Stainless steel construction •
- Tamper resistant •
- Static strength 1,500 lbs. •
- Dynamic strength 70 ft-lbs. •
- Endurance 1,000,000 cycles •
- Field selectable fail safe/fail secure •
- Dual voltage 12 or 24 VDC •
- Horizontal adjustment •
- Non-handed •
- Internally mounted solenoid •
- Accommodates up to 3/4" pullman latch •
- Five year limited warranty •

## Optional Features

- LBM - Latchbolt monitor •
- LBSM - Latchbolt strike monitor •

## Electrical

- .45 Amps @ 12VDC continuous duty •
- .25 Amps @ 24VDC continuous duty •

## Finishes

- 630 - Satin stainless steel •
- 605 - Bright brass •
- 606 - Satin brass •
- 612 - Satin bronze •
- 613 - Bronze toned •
- 629 - Bright stainless steel •

## Frame Application

- Metal •
- Wood •