

BioAxxis Development Corporation

Specifications

Heavy-Duty ANSI, UL-Latch
Audit Trail & Access Control

NOW AVAILABLE

BioAxxis® ThumbLock®



Standard Features

Fingerprints Accepted	1,000
Biometric Sensor Type	Optical
PIN Codes Accepted	1,000 (or 1,000 combo PIN/FP, per user per lock)
Mechanical Key Override	Yes
Cylinder Type	Standard replaceable 6-pin rim cylinder Schlage SC-4 keyway (3 keys included)
Latch Type	Heavy-Duty, ANSI & UL-listed tubular latch (adjustable backset)
Door Thickness	1-3/8 to 2-1/4 inch
Certifications	CE, FCC, ANSI, UL
Power Source	4 AA batteries (6v); Door can also be hard-wired
Battery Back-up	9V battery will provide power if keys are lost and AA batteries dead
Install Outdoors	Yes
Weatherproof	Yes
Handedness	Non-handed
Available Finishes	SC (US26D), SN (US15) , PB (US3), ORB (US10B)
Warranty	Two Years
Special Features	Fingerprint sensitivity verification mode (allows adjustment of FRR to make scanning of FP easier or harder); full suite of access control features, Open Mode, Impact alarm, and so much more
Audit Trail	Yes
Networking	No

Installation Rating

Handyman or Professional

Applications

High-End Residential; Mid-Duty Commercial
Outdoors and Indoors - full exposure to weather

Accessories/Upgrades

AT Upgrade (ATU) - 1GB flash memory and AT software
PCMU - ATU + FP scanner to centrally register & program all ACS features and use (1) flash drive to program all locks