



1Touch® IQ2

NO ADDITIONAL HOLES TO DRILL
3 WAYS TO OPEN: FINGER, CODE & KEY
INDOOR/OUTDOOR ANSI GRADE QUALITY

Since 2005, the 1Touch® series of locks have been the sales leader in the keyless door entry market. Over 10,000 locks being sold assures buyers they are purchasing the most secure, durable, trusted and convenient lock available. With its unique design, robust features, and unrivaled quality, the 1Touch® will surely remain the preferred security solution for years to come.

Stylish and easy to use, these keyless biometric door locks offer a sliding front panel that protects the fingerprint sensor against the outdoor elements. Once it is raised, the fingerprint scanner is activated and ready to use. Simply place your finger on the ultra-quick and reliable scanner and the door unlocks instantly.

The 1Touch® IQ2 is available in two configurations:

IQ2-AT: Accommodates up to 36 fingerprint users and 78 pin number users. This model is compatible with an USB Audit Trail Kit (sold separately). The Audit Trail Kit records the date and time each user comes through the door.

IQ2-HC: Accommodates up to 75 fingerprint users and 78 pin number users.

State of the art biometric security is only 10 minutes away! Installation is simple, typically requiring only a screwdriver. The 1Touch® IQ2 will fit a standard US door without modification to the door.

Both models include ANSI grade latches providing excellent dependability and 4 high security “dimple” keys for manual key override. This type of keyway is nearly impossible to pick.

Now you can use the unparalleled security of biometrics to assure only registered users have access to your home or office. The 1Touch® IQ2 provides freedom from lost or stolen keys! The numeric keypad and the fingerprint scanner allows users to be enrolled or deleted from the lock individually.


With its abundant features and unsurpassed value, this cost effective keyless entry solution is the answer to your home or business security needs. Buy one today and discover the 1Touch® IQ2 difference!




1Touch® IQ2

Available Finishes



Brushed Nickel



Antique Brass



Polished Brass



1TOUCH® IQ2 FEATURES

- New! - "Bump Resistant" High Security Dimple Keys
- Install your 1Touch® IQ2 in 10 minutes - no drilling needed!
- Fits a USA standard 2-1/8" diameter hole with a thickness of 1 3/8" - 2 1/4"
- Easily add or delete individual users directly on the lock (no PC required)
- 36 fingerprint user capacity (75 for High Capacity model) – 78 pin number users
- Fingerprint, Pin, or Key Access methods
- ALL weather design - Operating Temperature: -29 ° to 140 ° F
- ADA compliant handle
- 4 AA battery with approximately 15,000 uses before replacement
- Sliding weather cover triggers sensor to power on automatically
- Fingerprints will not be lost if batteries fail
- Low battery warning alert
- Includes both : 2 3/8 and 2 3/4 inch backsets (ANSI grade)
- Optional audit trail kit on 36 user model

* - Installation time is based on an approximation of a typical installation on a standard preparation door. Actual installation time will vary. All features and specifications are subject to change without notice.

SPECIFICATIONS

| | |
|---------------------------|--|
| Unlocking Methods | Fingerprint, Pin Codes and Manual Key Override |
| False Identification Rate | <0.0001% |
| Fingerprint User Capacity | 36 Standard Model* 75 High Capacity Model* |
| Password Capacity | 78 Max (less registered fingerprint users) |
| Password Length | 8 Digits |
| Door Thickness | 1 3/8" to 2 1/4" |
| Scanner Type | Optical CMOS |
| Resolution | 560 DPI |
| Verification Type | 1:N |
| Scanning Time | < 1 Second |
| Anti static Voltage | >15000v |
| Working Temperature | -29°F / 140°F |
| Power Supply | 4 AA |

* - 1Touch® IQ2's are available in a 36 user capacity model with audit trail capability support and a 75 user high capacity model **without** audit trail support. The model must be selected at time of purchase and cannot be converted to a different model. Specifications are subject to change without notice.