

SUPrema BioStation T2

Fingerprint IP Access Terminal with Face Detection



BioStation T2 | The new BioStation T2 blends loads of innovative features with Suprema's sophisticated fingerprint recognition technology. Its powerful dual-CPU engine ensures seamless operation and internal camera captures face image logs (snap shots) for extra level of security. Sealed in a at-panel front glass and rened dimensions, it provides intuitive and aesthetic GUI on easy-to-use touchscreen LCD. In addition to its extensive communication interfaces, BioStation T2 also supports embedded web server which provides convenience system management over its IP-based access control system.



BioStation T2

Fingerprint IP Access Terminal with Face Detection

Features

Intuitive Touchscreen GUI

5" touchscreen LCD with easy-to-use GUI

Face Detection Technology

Camera for face image capture

Embedded Web Server

Preloaded with BioStar Lite embedded web server

Ultra Performance

1:3,000 matches in one second, 200k users/1 million logs

Versatile Interfaces

PoE, WiFi, TCP/IP, RS485/232, Wiegand, relay

Video Phone

IP based video and audio interface or analog video phone

RF Card Options

EM, Mifare/DesFire

Secure I/O

- External Relay unit for secure door control and I/O expansion
- Encrypted communication for enhanced security

- * 16MHz 8 bit microprocessor
- * 4 digital inputs and 2 relay outputs
- * Dimension :
143 x 82 x 35 mm (W x H x D)


Intuitive Touchscreen GUI of BioStation T2



Specifications

CPU	667MHz RISC, 533MHz DSP
Memory	1GB ash, 256MB RAM
LCD	5.0 inch WVGA touchscreen
Fingerprint Sensor	Optical
Camera	Face detection & videophone
RF Card Options	25KHz EM, 13.56MHz Mifare
Template Capacity	400,000 (1:1), 20,000 (1:N)
Max User	200,000
Log Capacity	Fingerprint: 1,000,000 / Image: 5,000
PoE	Yes
Interfaces	Wireless LAN(optional), TCP/IP, Wiegand 2ch RS485, RS232, 4 x TTL I/O, 2 x Relay USB (Host & Slave), SD card slot
Tamper	Switch
Sound	16 bit Hi-Fi voice & sound indication
Operating Temp.	- 20°C ~ 50°C
Operating Voltage	12vDC
Dimensions (mm)	155(W) x 155(H) x 40(D)

System Configuration



Intelligent Biometric Controls, Inc.

601A Brooklyn Dr. Milford, OH 45150

Tel : 866-400-9292 Fax : 513-239-6328

E-mail : info@fingerprintdoorlocks.com Homepage: www.FingerprintDoorLocks.com

©2011 Suprema, Inc. Suprema and identifying product names and numbers herein are registered trademarks of Suprema, Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.